

U.S. ENVIRONMENTAL PROTECTION AGENCY

MEETS EPA PARTICULATE MATTER (Smoke) CONTROL
REQUIREMENTS FOR NON CATALYTIC WOOD HEATERS
BUILT ON OR AFTER JULY 1, 1990

SMOKE
THIS MODEL



0 (Grams Per Hour) 8.5

EFFICIENCY*



50% 60% 70% 80% 90% 100%

Wood heaters with higher efficiencies cost less to operate.

*(Not tested for efficiency. The value indicated is for
similar non-catalytic wood heaters.)

HEAT OUTPUT

11,800 to 38,200 BTU/HR

Use this to choose the right size appliance for your needs

ASK DEALER FOR HELP

This wood heater will achieve low smoke output and high efficiency
only if properly operated and maintained. See owner's manual.

7037-137

QUADRA-FIRE®

90.6%

TESTED OVERALL

EFFICIENCY

MODEL: 4300 Series ACC

THE CSA B415 STANDARD METHOD FOR MEASURING
THE EMISSIONS AND EFFICIENCIES OF RESIDENTAL
WOOD STOVES WAS USED TO TEST THIS MODEL FOR
ITS OVERALL EFFICIENCY RATING.

Manufactured by:



HEARTH & HOME
technologies

7037-138B

1

Listing and Code Approvals

A. Appliance Certification

Model:	4300 Millennium & Step Top (ACC) Uni-Body
Laboratory:	OMNI Test Laboratories, Inc.
Report No & Date:	061-S-67-6
Type:	Listed Room Heater, Solid Fuel Type
Standard:	UL1482 and ULC S627-00 and (UM) 84-HUD, Mobile Home Approved.

The Quadra-Fire 4300 Series Wood Stove (ACC) meets the U.S. Environmental Protection Agency's 1990 particulate emission standards.

B. Mobile Home Approved

This appliance is approved for mobile home installations when not installed in a sleeping room and when an outside combustion air inlet is provided. The structural integrity of the mobile home floor, ceiling, and walls must be maintained. The appliance must be properly grounded to the frame of the mobile home and use only listed double-wall connector pipe. Outside Air Kit, part OAK-ACC must be installed in a mobile home installation

C. Glass Specifications

This stove is equipped with 5mm ceramic glass. Replace glass only with 5mm ceramic glass. Please contact your dealer for replacement glass.

NOTE: This installation must conform with local codes. In the absence of local codes you must comply with the **UL1482, (UM) 84-HUD and NPFA211** in the U.S.A. and the **ULC S627-00 and CAN/CSA-B365 Installation Codes** in Canada.

Quadra-Fire is a registered trademark of Hearth & Home Technologies.

D. BTU & Efficiency Specifications

EPA Certified:	1.1 grams per hour
EPA Certificate Number and Date:	Number: 656 Issued: 02-05-2007
Efficiency:	79.82%
BTU Output:	11,800 to 38,300 / hr.
Heating Capacity:	1,500-2,400 sq ft depending on climate zone
Vent Size:	6 inches
Firebox Size:	2.4 cubic feet
Max Wood Length:	20 inches
Fuel:	Cord Wood
Shipping Weight:	355 lbs



⚠ WARNING

Fire Risk.

Hearth & Home Technologies disclaims any responsibility for, and the warranty will be voided by, the following actions:

- Installation and use of any damaged appliance.
- Modification of the appliance.
- Installation other than as instructed by Hearth & Home Technologies.
- Installation and/or use of any component part not approved by Hearth & Home Technologies.
- Operating appliance without fully assembling all components.
- Operating appliance without legs attached (if supplied with unit).
- Do NOT Overfire - If appliance or chimney connector glows, you are overfiring.

Any such action that may cause a fire hazard.

NOTE: Hearth & Home Technologies, manufacturer of this appliance, reserves the right to alter its products, their specifications and/or price without notice.