## Door and Glass Gasket Replacement Instructions

for all Jøtul Gasket Kits

## Contents:

- 3/8" Round Gasket
- 1/4" Round Gasket
- 1/4" Round Gasket (Self-adhesive)
- 3/16" Round Gasket (Self-adhesive)
- 1/8" x 5/16" Flat Gasket (Self-adhesive)
- Gasket Cement

## Tools Required:

- · Wire Brush
- Scraper
- Work Gloves
- Safety Goggles
- · Scissors or Utility Knife

Please read these instructions before beginning the installation procedures.

- Remove door(s) from the stove.
- Place doors on a work surface. Place cardboard or a drop cloth on the work surface to avoid damaging the door's finish.
- 3. Remove Glass Clips and Glass, if required. Note the orientation of the glass. Some stove models have a coated glass that must be reinstalled with the same face on the outside. Look for the imprint, "THIS SIDE OUT".
- 4. Scrape and brush the old gasket and cement from the door(s). For best results, remove all of the old cement.
- 5. Select the gasket(s) required for your stove model from the chart on the reverse side of this sheet. Lengths noted are approximate. Trim gasket as appropriate for the application.
- 6. Cut the tip 3/16" from the top of the cement bottle. CAUTION: Skin and eye irritant. Use gloves and eye protection when using gasket cement.

  (Note: Cement is not necessary for self-adhesive gaskets.)
- 7. Run a 3/16" bead of cement in the gasket channel. Keep the bead modest righter than 3/16" for the largest diarreter gasket.
- 8. Starting in the middle of one side, place gasket in the channel. DO NOT STRETCH THE CASKET /MATERIAL WHEN HANDLING. Trim excess to form a clean butt joint at the ends. Depending upon the application, the ends will either butt together or be secured under a glass clip. Once the gasket is in place, use your fingertips to push the material down to ensure that it is uniformly seated within the channel.
- 9. Allow the cement to air cure for at least 30 minutes.
- 10. Replace the glass clip gasket, if required, with 1/8" x 5/16" flat, self-adhesive gasket.
- 11. Reinstall the glass, glass clips, and doors.



Application	Part Number	Size	Approximate Length
F 600 Firelight Ash Door Gasket	200024	1/4 in.	3 ft. 9 in.
Door Casket Center	200024	1/4 in.	1ft.6 in.
Door Gasket (both)	100038	3/8 in.	7 ft.
Side Door Gasket	100038	3/8 in.	5 ft.
Glass Gasket (each)	129644	1/4 In. self-adhesive	3 ft. 6 in.
F 500 Oslo	129044	174 m. sen-adriesive	312.011.
Ash Door Gasket	200024	1/4 in.	4 ft.
Door Gasket	100038	3/8 in.	6 ft.
Side Door Gasket	100038	3/8 in.	4 ft. 6 in.
Glass Gasket	100038	3/8 in.	5 ft.
Glass Clip Gasket	127215	1/8 in. x 5/16 in. flat	1ft.4in.
F 400 Castine	1	<u>                                     </u>	
Ash Door Gasket	100038	3/8 in.	3 ft. 6 in.
Single Door Gasket	100038	3/8 in.	6 ft.
Left Door	100038	3/8 in.	3 ft.
Right Door	100038	3/8 in.	4ft.
Single Door Glass Gasket	129644	1/4 in. self-adhesive	5 ft.
Glass, Left Door	200028	3/16 in.	3 ft.
Glass, Right Door	200028	3/16 in.	3 ft.
Glass Clip Gasket	127215	1/8 in. x 5/16 in. flat	8 in.
F 118 CB Black Bear			
Door Gasket •	100038	3/8 in.	3 ft.
			2 ft.
Glass Gasket	200028	3/16 in. 1/8 in. x 1/4 in. flat	1 ft.
Glass Clip Gasket F 3 CB	127215	770 H. X 174 H. Hat	THE
Door Gasket	100038	3/8 in.	5 ft.
Nale Dear Carlot	200024	1/4 in.	2 ft. 6 in.
Glass Gasket	200024	1/4 in.	3 ft. 6 in.
Glass Clip Gasket	127215	1/8 in. x 5/16 in. flat	1ft.
F 100 Nordic		A Company of the Comp	-4.6:-
Door Gasket	100038	3/8 in.	5 ft. 6 in.
Glass Gasket	200024	1/4 in.	5 ft. 8 in.
Glass Clip Gasket	127215	1/8 in. x 5/16 in. flat	• III.
F 602 CB Door Gasket		1/4 in.	3 ft.
Glass Gasket	200024	3/16 in.	2 ft.
Glass Gasket		1/8 in. x 5/16 in. flat	2 ft.
·	127215		
Glass Clip Gasket	127215	1/8 in. x 5/16 in. flat	1ft.
C 550 CB Rockland			
Door Gasket	100038	3/8 in.	7 ft. 9 in.
Glass Gasket	129644	1/4 in. self-adhesive	5 ft. 6 in.
Glass Clip Gasket	127215	1/8 in. x 5/16 in. flat	1 ft. 4 in.
C 450 Kennebec & Tamarack			
Front Doors	100038	3/8 in	9 ft. 6 in.
Double Door Glass Gasket	129644	1/4 in. self-adhesive	7 ft.
Single Door Glass Gasket	129644	1/4 in. self-adhesive	7 ft.
Glass Clip Gasket	127215	1/8 in. x 5/16 in. flat	1 ft. 4 in.
C 350 Winterport			
Front Door	100038	3/8 in.	6ft.
Glass Gasket	129644	1/4 in. self-adhesive	4 ft. 6 in.
Glass Clip Gasket	127215	1/8 in. x 5/16 in. flat	1 ft. 4 in.
C 370 USA			
Doors Gasket	100038	3/8 in	7 ft.
	200024	1/4 in.	6.5 ft.